

# WhaleSpray

## Technical Data Sheet

### WS 1805 S

Family: 1  
Product code: 1805S00



Creation date: 02/11/2014  
Review date: 16/09/2016  
Página: 1 de 1

## DESCRIPTION

Ceramic Antispatter.

**WS 1805 S**, innovative ceramic protective coating for welding processes. With a single application it forms a dry film which effectively protects welding equipment for up to 8 hours. No cleaning of equipment required which reduces costs and improves productivity. Compatible with painting processes.

## CHARACTERISTICS AND ADVANTAGES

- Ceramic coating, oil-free.
- Increases productivity by 11%.
- The film applied dries in seconds.
- Reduces consumable costs by up to 70%.
- Protective film offers outstanding adhesion.
- Protects nozzles, contact tips and jigs.
- A single application offers protection for an entire shift.

## APLICACIONES

- MIG-MAG Welding.
- Laser and plasma cutting.
- Protection of surfaces.
- Jigs, parts and all types of accessories.

## HOW TO USE

- Shake the aerosol vigorously, unscrew the nozzle, spray over the pieces to protect, attach the nozzle and spray over the inside and outside.
- Drain upside down after use.

## TECHNICAL DATA

Colour		White
Density		2200 kg/m <sup>3</sup>

FORMATS:  
Spray



**WhaleSpray**  
Spray everything

[www.whalespray.com](http://www.whalespray.com)

P.I. Ametlla Park · c/ Aiguafreda, 24  
08480 L'Ametlla del Vallès · Barcelona  
Tel. 900 15 20 40

Síguenos en:  

 Empresa Certificada ISO 9001-ISO 14001  
Company certified ISO 9001-ISO 14001